

Technical informations

Quadro Line

Code	264-0000000001
Name	"Z" monobloc locker
Dimensions (WxDxH)	810x500x1800 mm
Inside Dimensions (WxDxH)	418/210x480x1140 mm
N° places	4
N° places for column	2
Material	DC01/FeP01 UNI EN 10130
Weight (Kg)	45
Volume (m3)	0,72



General Informations

Base and corpus Base on steel feet, h. 120 mm. with anti-oxidation plastic inserts, predisposed for the adjustable feet. Reinforced ribs for the base interlocking. Corpus in one bended panel with perforations between roof and back for ventilation and sides front thickness 30 mm. with anticut folded edges on tree levels

Door Doors fitted with intenal hinges with external pin with 180 ° rotation, reinforce on the hinges side and anticut bend on tree orders on the remaining sides, squared holes for ventilation ,squared handle with label holder.

Lock Cylinder lock typo Yale with double key.

Closing One way lever

Inside Upper dorr with upper half shelf and h.500 mm. from the roof bottom ta h 1140 mm from the bottom , steel clothes hanger bar with plastic support with hook .Left door with clothes hanger bar roof at h 1140 drom the bottom and right side h. 495 mm.

Colour door Painting with epoxy powder color RAL 7035.

Colour corpus Painting with epoxy powder color RAL 7035.

Law In specification D.Lgs.81/2008, EN UNI ISO 9001, EN UNI ISO 14001, UNI tests on product and finishing.

Possibilities

Base On base, inox feet, without feet.


door Without ventilation, with grid, HPL or plexiglass.

lock padlock handle, embedded padlock, mechanic combination ,electronic combination and coin lock (€1,00).

closing -

Inside upper and lower shelf

Corpus / door color



Technical informations

Code **264-0000000001**

Accessories.

Sloping roof

Support bench

Kit "S"hooks

Adjustable feet

Padlock

Anti-corrosion cover for feet

Spare parts

Cylinder lock type Yale with double key

Padlock handle

"Z" upper door h. 1130mm, "Z" lower door h.1130 mm.

Certifications

UNI 9115/87 Erosion Taber

UNI 9428/89 Resistance to scratches

UNI 9429/89 Resistance to sudden changes in temperature

UNI 9300/88 e FA 276/89 Tendency to get dirty

UNI 9427/89 Resistance to light

UNI 9149/89 Mirror-like reflection

UNI EN ISO 9227/2006 Resistance to corrosion

UNI 8901/86 Resistance to slamming

UNI EN ISO 1520/95 Resistance trials

UNI 10782/1999 Hardness test- Pencil method

UNI EN ISO 2409/2007 Grid test

This technical sheet is exclusive property of Armet Srl.

Reproduction is forbidden within the law (art.171 Law 22/04/1941 ,n.633).

The fraudulent use, without proper written authorization, even partial and by whatever means, will be protected according to law.

The foregoing text contains information reserved to the intended recipient.

The content of this e-mail is confidential and its confidentiality is legally protected by DL196/03

ARMET S.R.L. A Socio Unico- Sede Legale: Via IV Novembre, 2 - 43056 San Polo di Torrile (PR) - ITALIA
Capitale Sociale € 1.000.000 int. Vers - R.E.A.272345 - Registro Imprese Parma e C.F. 92192580345 - P.IVA 02854460348

